PS PROGRESSIVE SYSTEMS INC.

L-1850 JACK HAMMER

Product Description

L-1850 Jack Hammer is a high caustic, foaming alkaline cleaner, formulated for the rapid removal of baked on, carbonaceous soils. Excellent cleaning action gives superior results on stainless steel equipment, oven surfaces with baked on soils, painted transportation equipment, concrete surfaces, machinery, industrial soils, and on all types of food contact surfaces. Authorized for use in federally inspected meat and poultry plants. Not for use on zinc and highly polished or anodized aluminum surfaces.

Directions For Use

Foam Cleaning - Remove all food products from the area to be cleaned. Dilute at 2-10 ounces per gallon of water depending on the degree of soiling. Apply with foaming equipment and adjust the cleaner concentration to rapidly remove the soils. Allow the foam to remain on the surface for 2-5 minutes. If required, brush the heavily soiled areas. Rinse away the loosened soil with hot or cold water to leave the surface clean.

Steam and Pressure Cleaning - use 1 to 5 ounces per gallon depending on the amount and type of soil. Follow machine manufacturer's instructions for proper application. After cleaning, rinse with either low or high pressure potable water.

Cautions

Specifications Odor Mild Musty Clear, Amber Appearance Liquid pH (1.0% solution) 13.5 (approx.) Specific Gravity (H²O=1) 1.270 + 0.005 Foaming Copious Flash Point None Solubility in Water Complete

DANGER. KEEP OUT OF REACH OF CHILDREN. Contains Potassium Hydroxide. Can cause severe burns to eyes, skin, and mucous membranes. Contact with eyes can cause permanent eye damage. Inhalation if mist or spray can cause severe lung damage. Avoid contact with eyes, skin and clothing.

First Aid: Eyes: Flush immediately with water for at least 15 minutes. If irritation persists, see a physician. Skin: Remove contaminated clothing. Wash from skin with plenty of water. Wash contaminated clothing before reuse. If irritation persists, consult a physician. Ingestion: Do NOT induce vomiting. Have person sip a glass of water. Seek immediate medical attention. For more safety and handling instructions, see Material Safety Data Sheet.

Visit us at www.progressivesystemsinc.com

P.O. Box 35 • 25 Hickory Street • Frankford, DE 19945 Phone: 302-732-3321 • Fax: 302-732-9640

MATERIAL SAFETY DATA SHEET (Prepared According to 29 CFR 1910.1200)

SECTION 1: PRODUCT IDENTIFICATION			
Distributor: Progressive Systems Inc.		Emergency Phone Number: (302) 732-3321	
Address: P.O. Box 35 - 25 Hickory Street Frankford, Delaware 19945			
Trade Name: L-1850 Jack Hammer		Product Type: Cleaner and Aluminum Brightener	
SECTION 2: HAZARDOUS INGREDIENTS			
CHEMICAL NAME / COMMON NAME	C.A.S. NUMBER	PERCENT (OPTIONAL)	TLV (SOURCE)
Potassium Hydroxide	1310-58-3		2 mg/m ³ (ACGIH)
1			
SARA HAZARD TITLE III, SECTION 323: Contains the starred (*) ingredients at the indicated percentages. Other ingredients in this product are: 🗶 Less than 1.0 % by weight or 0.1% for carcinogens 🗶 Not Hazardous 🗶 Declared to be Trade Secret			
SECTION 3: PHYSICAL DATA			
Boiling Point (° F): Near 212	Specific Gravity (H2	2O = 1): 1.270 <u>+</u> 0.005	pH (1.0% solution): 13.5 (approximately)
Vapor Pressure (mm Hg): Not determined Vapor Density (air = 1): Not determined			
Solubility in water: X Complete Insoluble Emulsifiable (or Dispersible) Slight (or Partial)			
Evaporation Rate (vs. Water): Faster Slower X About the same			
Appearance and Odor: Clear, Amber Colored Liquid. Slight detergent odor.			
SECTION 4: FIRE AND EXPLOSION HAZARD DATA			
		Flammable Limits: Upper - Not Established Lower - Not Established	
Extinguishing Media: As appropriate for surrounding fire. CO ² , Dry Chemical Foam, Water Spray. Water spray to cool drums and prevent rupture.			
Special Firefighting Procedures: Do not enter confined fire spaces without appropriate protective gear and self-contained air supply.			
Unusual Fire or Explosion Hazards: None known.			
SECTION 5: STABILITY AND REACTIVITY DATA			
Stability: Product is stable. Polymerization: Will not occur			
Hazardous Decomposition Products: Carbon monoxide Incompatibility: Strong Acids, Oxidizers			
SECTION 6: HEALTH HAZARDS			
Primary Routes of Exposure: X Eye X Skin X Oral X Inhalation Other			
Signs and Symptoms of Over exposure (Acute): Eyes and skin: Can cause severe irritation, even burns, depending on duration of exposure. Ingestion: Pain and inflammation of the mouth, pharynx, esophagus and stomach. Causes erosion of the mucous membranes, especially the stomach. Vomiting will usu- ally occur. Inhalation: Do not concentrate and inhale vapors. None from vapors or mist with proper ventilation.			
Signs and symptoms of overexposure (Chronic): None known Medical Conditions Aggravated by Overexposure: None known			
SECTION 7: EMERGENCY AND FIRST AID PROCEDURES			
Eyes: Flush immediately with water for at least 15 minutes. Call a physician. Skin: Flush immediately with water for at least 15 minutes. Call a physician.			
Ingestion: Give large quantities of water. Do not induce vomiting. If vomiting occurs, keep head below hips to avoid aspiration. Never give anything by mouth to an unconscious person. Seek immediate medical attention.			
Inhalation: Remove exposed person to fresh air. Treat symptomatically.			
SECTION 8: SPECIAL PROTECTION INFORMATION			
Respiratory Protection: Not needed under normal conditions of use. Eye Protection: Safety Glasses/Goggles Protective Gloves: Rubber, Nitrile			
Ventilation Requirements: X Local Exhaust X Mechanical Room Ventilation is adequate.			
SECTION 9: SPILL OR LEAK PROCEDURES			
Steps to be Taken if Released or Spilled: Flush spill area with water. For large spills, contain spill, then pick up with mop, wet-vac, or absorbent. Wash residue to sewer. Non toxic and biodegradable. Waste Disposal Method: Dispose of in accordance with Federal, State and Local ordinances.			
SECTION 10: STORAGE AND HANDLING INFORMATION			
Precautions to be Taken in Handling and Storage: Do not get in eyes, on skin or clothing. Do not mix with other chemicals. Use with adequate ventilation. Wash thoroughly after handling. Avoid breathing mists or vapors. Keep container closed. Store in a cool, dry place away from strong acids.			
The health hazards given on the Material Safety Data Sheet apply to this product in its concentrated form (as supplied) and may differ significantly at use dilution. The signs and symptoms of overexposure apply only to negligence in handling or misuse of the concentrated product and not to the routine exposure to the product under normal condition of use.			
Date Prepared: 2/11/20	13 Supersedes:	: 5/18/2006 Code: L	-1850 Jack Hammer